

**Type "O" Series Cylinder Single Stage Regulators
Extra Heavy Duty**

**VICTOR®
Professional**



**APPLICATION AND USES
Type "O" Cylinder Regulator**

- Extra heavy duty applications
- Single stage design.
- Heavy duty steel Gauge Guard (GG) available for all "O" cylinder regulators

DESIGN/CONSTRUCTION

- 3" stainless steel diaphragm
- Multi-Seat 4 way seat block
- "Positive Pressure" yoke type regulation
- Inlet pressures up to 5500 PSIG/ 380 bar
- "Safe-T-Check" helps to prevent damage due to pressure surge
- 2-1/2" brass gauges
- Easily replaced cylinder coupling with body nut
- 8 bolt bonnet construction

Model No.	CGA Inlet Connection	Delivery Range (PSIG/ Bar)
"O"	540	60/4.4

Weight: 6.25 lbs. (2.8 Kg) with Gauge Guard 7.25 lbs. (3.3 Kg)

Gas Service	Model No.	Delivery Range (PSIG/ Bar)	Part No.
Oxygen	"O"-CGA 540 (GG) <i>(Gauge Guard)</i>	120/ 8.3	5655-6527
Oxygen	"O"-CGA 540	120/ 8.3	5255-6521
Outlet Connections: Cylinder Type 9/16" - 18 (M)			

Note: Acetylene regulators with alternate inlet connections are available. Please specify when ordering. For maximum safety, always use flashback arrestors and/or reverse-flow check valves.

Gauge Guard: 5635-5307



"O" Series with Gauge Guard (GG)

Meco® Series Regulators • Extra Heavy Duty